



Over **60** years of consistent excellence

Computerized Touch Screen Vickers Hardness Testing Machine

Model: VM 50-TS



ntation Size

Wide Testing Range from Soft metal to medium hardness Steel.



High accuracy & repeatability of measurement at all loads.



Front Panel Touch Screen Display



USB Connectivity





Computerized Touch Screen Vickers Hardness Testing Machine

Model: VM 50-TS

Features:

- Fully Computerized Touch Screen Vickers Hardness Testing Machine.
- Accurate Measurement of Vickers Hardness number using "State of the art" image processing technology.
- Wide testing range : from soft metal up to hardest.
- High accuracy & repeatability of measurement at all loads.
- Faster measurement yielding to higher productivity.
- Small size of indentation makes it a non destructive testing on finished components.
- Motorised loading and unloading cycle.
- Small loads allow testing of thin sheet metals.
- Advanced windows based software
- PLC based system
- Inbuilt branded touch screen laptop.
- Front panel touch screen display.

Latest GUI features:

- User Friendly software with windows features.
- Online indentation setting & focussing on front touch screen display.
- Advance image processing: algorithms implemented for precise calculation of hardness numbers with various options to cover all ranges of specimen.
- Batch file processing : Option for data storage & reports generation.
- Statistical Evaluation: Software for calculating standard deviation, mean, median, histogram etc.
- Wide options in calibration mode calibration/verification on PC monitor makes easier to operate.
- USB Printer/Wi-fi printer port for printer interface with result & graph print-out.
- Facility to test in Manual, Semi-automatic & Automatic Mode.
- Facility to export result/data in PDF format.

Application:

'FIE' touch screen Vickers hardness tester is a simple and accurate means to produce and automatically measure the indentation to give Vickers hardness number.

These testers are suitable for measuring the hardness of precision metallic parts with wide testing range from soft to hard and their accurate results are widely acclaimed.

These testers strictly confirms to IS 1501-2:2013

Construction:

The robust machine frame is designed to accommodate the high precision loading equipped with front touch screen laptop.

Specimen is placed on a testing table. The test cycle is semi automatic.

The accurate load is applied on a diamond indenter by means of lever and weights. After a specific lapse of time the load is released automatically.

The image is digitalized using USB camera fitted in the machine & is captured by the front touch screen laptop.

The diagonals of the indentation are automatically measured by software to give the Vickers hardness number.

The machine is equipped with latest touch screen branded laptop so their is no need to arrange for computer.



For Auto Turret Machine after clicking on cycle start button indexing mechanism will operate automatically & loading mechanism starts, once loading finishes again indexing mechanism will positioned at measuring station.

Technical Specifications:

Test Loads	5, 10, 20, 30, 50 kgf.
Maximum Test Height (mm)	200
Scale least count (mm)	0.001
Diagonal measuring range (mm)	0.05 to 0.3
Throat Depth (mm)	135
Machine Dimensions	L600 x W440 x H920 Approx.
Weight	100 Kg. Approx.
Power Supply	220VAC, 50Hz, 1-Ph.

Standard Accessories:

Standard Test Block	1 No.
Diamond Indenter	1 No.
Weights	1 Set
Flat Anvil	1 No.
Vee – type anvil (Small & Big)	1 No. Each
Spanners	1 Set
Software CD	1 No.
Telescopic Cover	1 Set
Instruction Manual	1 Book

Computerized Touch Screen Vickers Hardness Testing Machine

Model: VM 50-TS

Touch Screen Software Package includes :




Home Page






Impression Measurement




Statistics



Batch Analysis

Building	tes	DESCRIPT.				
Discours. Modern	191.00 (M.	Tipe (dec	See 1	-		
Self-	inter	Not sel Year (A)(Th)				
Descripe.	6 300 0 and	Type Ame	Name of	-	E harin	ii e
East -	-Only I	Box sel Size:				
Consider Markets	10 (00 (00 m))	Tops down	Stores			_
bed.	retail	See and Year o			Dens	6
Discourse.	MARKETON TO STATE OF THE PARTY	Tipe (Ass)	See 1	-	200	-
ties.	stel	Non-sed Steel				
Desirios Brokeni	6.3676/7vew 206.9677.96	Tipe Am-	Name of	-		_
East	State	Downell Time :				
Disease.	100000	Ton Steed Section	toeen	1001		7. T
	Load for the free control of the first feet for the free control of the free control o	Lied (H light for the control of the	Description	Description	Description Description	Description

Readings with impression



Series: VM 50-TS



Over **60** years of consistent excellence

Manufactured By:

Fuel Instruments & Engineers Pvt. Ltd.

Sold And Service By: SUZKI INSTRUMENTS

Cell 9594084085 /8000976140 E-Mail: sales@simaterialtestingservices.com

Web: www.simaterialtestingservices.com